

# NLZ<sup>®</sup> Electric Motor



## Seamless integration. Increased control.

The NLZ electric motor offers a more responsive and capable solution for your operatory. When coupled with the A-dec<sup>®</sup> touchpad's intuitive power display and programmable memory, you can fully integrate your delivery system and place your focus where you need it—on your patients.

With the NLZ on your A-dec delivery system, you'll enjoy a clutter-free operatory and get all-in-one access to:

- Improve control, productivity and ease.
- Eliminate reaching, twisting and turning.
- Program the settings to match your preferences.
- Monitor speed and switch between forward and reverse.



NLZ electric motor—for high- and low-speed applications, including endodontics.



Integrated power and control are at your fingertips with the A-dec touchpad.

## Natural feel. Exceptional usability.

There's a reason the NLZ motor features a titanium design. It's 30% lighter than stainless steel, yet more durable—for a natural tactile sense and exceptional usability. With applications ranging from high-speed gross reduction and low-speed precision finishing to specialty functions such as endodontics, the NLZ motor helps you achieve greater precision and treat patients more efficiently.

**Minimize fatigue:** The titanium design is comfortably lightweight, for balanced handling.

**Increase performance:** Enjoy a full range of speed, with all the power you need.

**Operate with precision and consistency:** Program settings for activation, speed, torque and direction.

**Do more in less time:** Handpiece activates as you lift from the holder so you can view display as needed.

**Reduce cleanup and extend product life:** The motor is brushless and fully autoclavable.

**Light up the procedure:** Built-in, daylight-quality illumination gives you a clear view.



Details	NLZ
Applications	General restorative, prophylaxis, endodontics
A-dec Delivery System	A-dec 500 Pro/A-dec 500/A-dec 300 Pro/A-dec 300/A-dec 200
Micromotor Controller*	NLZ BA
Micromotor & Tubing	A-dec NLZ (factory) or NSK® NLZ (in-field installation)
Contra-angle Compatibility	E-Type
Motor Type	Brushless Micromotor
Speed (Standard Mode)	1,000–40,000 min <sup>-1</sup>
Speed (Endo Mode)	100–5,000 min <sup>-1</sup>
Torque (Standard Mode)	Max. 4.0 Ncm
Torque (Endo Mode)	Max. 3.0 Ncm
Weight	57g (micromotor only)
Light	Daylight-quality

\* An electric motor controller is a required component of the A-dec delivery system, which is configured at the time of your A-dec purchase.

### A-dec Headquarters

2601 Crestview Drive  
Newberg, Oregon 97132 USA

**P:** 1.800.547.1883 within USA/CAN

**P:** +1.503.538.7478 outside USA/CAN

**a-dec.com**

### Other Locations:

A-dec Nashville Experience Center

A-dec Australia

A-dec United Kingdom

Any colors and products shown may vary and are subject to change without notice. Contact your authorized A-dec dealer for the most current product information. All trademarks in this document are subject to the trademark rights of A-dec, its affiliates, and their collective suppliers in the United States and foreign countries.

©2024 A-dec Inc. All rights reserved.  
85.0299.25/E-only/1-24/RevA